

**Capilla®**

Wall Covering



Characteristics	Standards	Units	Capilla®
Indoor Air Quality	CA Section 01350 ( $\leq 0.5 \text{ mg} / \text{m}^3$ )	Floorscore Certified (SCS - FS - 04547)	Yes
Description			
Type of wall covering	EN 15102	Classification Norm	Vinyl Wall Covering
Special treatment			PUR
Overall thickness	ISO 24346 - EN 428	mm	1.00
Thickness of wear layer	ISO 24340 - EN 429, ASTM F410	mm	1.00
Weight	ISO 23997 - EN 430	g/m <sup>2</sup>	2000
Sheet size	ISO 24341 - EN 426	m (width)	2
		m (length)	20
		m <sup>2</sup> (surface area)	40
Dimensional stability	ISO 23999 - EN 434	%	$\leq 0.40$
Flexibility	ISO 24344 - EN 435	20mm mandrel	< 20
	ASTM F137		Pass
Seam Strength	ISO 16906	N/50mm	Pass
Residual indentation	ISO 24343 - 1 - EN 433	mm	$\leq 0.10$
Colour fastness to light	EN ISO 105 - B02	Degrees	$\geq 6$
	ASTM F1515	$\Delta E \leq 800$ after 300 hours (colour change)	Pass
Heat Stability	ASTM 1514	$\Delta E \leq 0.80$ (colour change)	Pass
Reaction to fire	EN 13501-1 : 2007+A1	Class	Bfl - S1
	ASTM E 648	Type	1
Smoke density	ASTM E 662	Dm	< 450
Stain & chemical resistance	ISO 26987 - EN 423	Index	0 (Excellent resistance)
	ASTM F925	Resistance	Pass
Fungi & bacteria resistance	ISO 846 A, C		Does not favour growth

