

# Homogeneous Vinyl Flooring

## Talitha®

The less you say, the more you can say with it. Earthy hues and minimalist textures complement almost any design scheme you can think of from the cool and contemporary to the warm and classic.



2349-751-4



2349-753-4



2349-757-4



2349-756-4



2349-758-4



2349-762-4



2349-755-4




2349-760-4

### Key Features:

- No Wax, No Polish
- Polyurethane Reinforced (PUR)
- Low Costs
- Durable & Tough
- Available in 1.5mm, 2.0mm & 3.0mm Sheet & Tiles

### Applications:

- Warehouses
- Exhibition Centers
- Porta Cabins
- Budget Hotels
- Storage Areas etc.



Welding Rod No. Talitha
WR 2349-751-4
WR 2349-753-4
WR 2349-757-4
WR 2349-756-4
WR 2349-758-4
WR 2349-762-4
WR 2349-761-4
WR 2349-755-4
WR 2349-760-4
WR 2349-754-4
WR-Clear



2349-761-4



2349-754-4

# Homogeneous Vinyl Flooring

## Talitha® Classic



Available in 1.00 mm.



4349-381-4



4349-382-4



4349-383-4



4349-384-4



4349-386-4



4349-387-4



4349-388-4




4349-389-4



4349-390-4



4349-391-4



Welding Rod No. Talitha Classic
WR 4349-381-4
WR 4349-382-4
WR 4349-383-4
WR 4349-384-4
WR 4349-386-4
WR 4349-387-4
WR 4349-388-4
WR 4349-389-4
WR 4349-390-4
WR 4349-391-4
WR-Clear

# Homogeneous Vinyl Flooring

Don't trust your feet to tell you where you are.

Malls, hospitals, laboratories, offices, industries and schools all look for the same sort of things in their flooring. Toughness, Durability, Low maintenance costs, and the ability to resist stains, bacteria and fungus. Characteristics you'll find in four elegant ranges of PUR-reinforced homogeneous vinyl flooring. The practical choice your feet will encounter almost everywhere they go.



The solution to every flooring need

Talitha® Talitha® Classic

Homogeneous Vinyl Flooring

Talitha®	Technical Data	Talitha® Classic
<ul style="list-style-type: none"> <li>Homogeneous Vinyl Flooring</li> <li>Polyurethane Reinforced</li> </ul>	<b>GENERAL PERFORMANCE:</b> EN 685 : 1996 EN 649 : 1997	<ul style="list-style-type: none"> <li>Homogeneous Vinyl Flooring</li> <li>Polyurethane Reinforced</li> </ul>
1.50 mm 2.00 mm 3.00 mm	<b>THICKNESS:</b>	EN 428 1.00 mm
1.5mm: 2m x 15m = 30m <sup>2</sup> 2.0mm: 2m x 15m = 30m <sup>2</sup> 3.0mm: 2m x 15m = 30m <sup>2</sup>	<b>SHEET:</b>	EN 426 1.0mm: 2m x 20m = 40m <sup>2</sup>
610mm x 610mm	<b>TILES:</b>	EN 427 610mm x 610mm
1.5mm: 2.65 kg/m <sup>2</sup> (Max.) 2.0mm: 3.50 kg/m <sup>2</sup> (Max.) 3.0mm: 5.25 kg/m <sup>2</sup> (Max.)	<b>WEIGHT:</b>	EN 430 1.0mm: 1.70 kg/m <sup>2</sup> (Max.)
Class Bfl-S1 ≥ 8 kw/m <sup>2</sup> Pass Type I	<b>REACTION TO FIRE:</b>	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2 ASTM E648-06 Class Bfl-S1 ≥ 8 kw/m <sup>2</sup> Pass Type I
< 20mm Pass	<b>FLEXIBILITY:</b>	EN 435 ASTM F137 < 20mm Pass
Class DS R10	<b>SLIP RESISTANCE:</b>	EN 13893 DIN 51130 Class DS R10
Wear Group P Pass	<b>ABRASION RESISTANCE:</b>	EN 660-2 ASTM D3384 Wear Group P Pass
< 0.1 mm Static load 800 psi	<b>RESIDUAL INDENTATION:</b>	EN 433 ASTM F970 < 0.1 mm Static load 800 psi
Continuous Use	<b>CASTOR CHAIR:</b>	EN 425 Continuous Use
> Blue Wool Standard 6	<b>LIGHT FASTNESS:</b>	EN 20105: B02 > Blue Wool Standard 6
1.5 mm, 2.0 mm, 3.0 mm	<b>WEAR LAYER THICKNESS:</b>	EN 429 1.0 mm
< 2.0 kV	<b>ELECTRICAL BEHAVIOR (body voltage):</b>	EN 1815 < 2.0 kV
<0.4 mm	<b>DIMENSIONAL STABILITY:</b>	EN 434 <0.4 mm
Good Resistance	<b>STAIN and CHEMICAL RESISTANCE:</b>	EN 423 Good Resistance
< 450	<b>SMOKE DENSITY:</b>	ASTM E 662-05 < 450
Does not favor growth	<b>FUNGI and BACTERIA RESISTANCE:</b>	Does not favor growth
Class A - non-shedding Suitable for use in following classes of clean room : ISO 1466-11999 Class 4	<b>CLEAN ROOMS:</b>	ASTM F51/68 Class A - non-shedding Suitable for use in following classes of clean room : ISO 1466-11999 Class 4
Annex 1 Part 2 (Smoke & Toxicity) Part 5 (Spread of Flame) and Annex 2 (Surface Flammability / Heat Release) 1121	<b>MARITIME USAGE:</b>	IMO RES A 653 (16) IMO MSC 61(67) US Coast Guard Approved Marine Equipment Directive 1121
10 Shades	<b>COLOURS AVAILABLE:</b>	10 Shades

For more details/ clarification regarding technical specifications, handling and installation, please contact Responsive Flooring.  
 Note: The samples shown are representative. For technical reasons the material may vary in shades and appearance.  
 The pattern given are with their product codes.



Eucharistic Congress Building No.I, 5 Convent Street, Colaba, Mumbai 400 001, India.  
 • India: Tel. +91 22 6656 2727 / 6656 2704 • India: Fax +91 22 6656 2798 / 6656 2799  
 • USA: Tel. +1 732 7592843 • United Kingdom: Tel. +44 208 8199711  
 • France: +33 1706 15499 • Australia: Tel. +61 29 0378599  
 • E-mail: enquiry@responsiveindustries.com • URL: www.responsiveindustries.com