

Heterogeneous Vinyl Flooring

Zeta® Wood Essence

Life began in wooded forests. In this collection, light, natural wood textures spring to life across a spectrum of dark and light wood shades. A faux-wood collection that's complete in itself.



Key Features:

- No Wax, No Polish
- Wear Layer Polyurethane Reinforced (PUR)
- Real Life Wood Patterns
- Low Maintenance
- Available in 2.0 meter width Sheet



9275-804-4



9275-805-4



9275-806-4



9275-807-4



9275-808-4



9275-809-4



9275-801-4



9275-810-4



9275-811-4



9275-812-4

Welding Rod No.
Zeta Wood Essence

WR 9275-801-4
WR 9275-802-4
WR 9275-803-4
WR 9275-804-4
WR 9275-805-4
WR 9275-806-4
WR 9275-807-4
WR 9275-808-4
WR 9275-809-4
WR 9275-810-4
WR 9275-811-4
WR 9275-812-4
WR 9275-813-4
WR 9275-814-4
WR 9275-815-4
WR-Clear



9275-802-4



9275-803-4



9275-813-4



9275-814-4



9275-815-4

Heterogeneous Vinyl Flooring

Isn't it interesting how people only notice a floor when they slip on it?

It used to take a fall to bring a floor to people's notice; until now. Introducing six stunning new ranges of heterogeneous vinyl flooring, in contemporary multi-coloured designs and realistic wood-pattern finishes. But the story doesn't end there. This flooring is PUR-reinforced, and therefore tough and durable. Plus it repels stains, bacteria and fungus with ease. So you see, the art isn't just in the looks.



Zeta® Wood Essence

Heterogeneous Vinyl Flooring

Technical Data		Zeta® Wood Essence
GENERAL PERFORMANCE: EN 685 : 1996 EN 649 : 1997		<ul style="list-style-type: none"> Heterogeneous Multi-Layered Vinyl Flooring Wear Layer Polyurethane Reinforced
THICKNESS:	EN 428	2.00 mm 3.00 mm
SHEET:	EN 426	2.0mm: 2m x 15m = 30m ² 3.0mm: 2m x 15m = 30m ²
TILES:	EN 427	610mm x 610mm
WEIGHT:	EN 430	2.0mm: 3.50 kg/m ² (Max.) 3.0mm: 5.25 kg/m ² (Max.)
REACTION TO FIRE:	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2 ASTM E648-06	Class Bfl-S1 ≥ 8 kw/m ² Pass Type I
FLEXIBILITY:	EN 435 ASTM F137	< 20mm Pass
SLIP RESISTANCE:	EN 13893 DIN 51130	Class DS R9
ABRASION RESISTANCE:	EN 660-2 ASTM D3384	Wear Group T Pass
RESIDUAL INDENTATION:	EN 433 ASTM F970 ASTM F1914	< 0.1 mm Pass Pass
CASTOR CHAIR:	EN 425	Continuous Use
LIGHT FASTNESS:	EN 20105: B02 ASTM F1515	> Blue Wool Standard 6 Pass
WEAR LAYER THICKNESS:	EN 429 ASTM F410	0.50 mm, 0.70 mm Pass
ELECTRICAL BEHAVIOR (body voltage):	EN 1815	< 2.0 kV
DIMENSIONAL STABILITY:	EN 434	<0.4 mm
STAIN and CHEMICAL RESISTANCE:	EN 423 ASTM F925	Good Resistance Pass
THERMAL RESISTANCE:	ISO 8302 (EN 12664) ASTM 1514	< 0.00752 m ² K/W Pass
SMOKE DENSITY:	ASTM E 662-05	< 450
FUNGI and BACTERIA RESISTANCE:		Does not favor growth
CLEAN ROOMS:	ASTM F51/68	Class A - non-shedding Suitable for use in following classes of clean room.
MARITIME USAGE:	IMO RES A 653 (16) IMO MSC 61(67) US Coast Guard Approved Marine Equipment Directive	Annex 1 Part 2 (Smoke & Toxicity) Part 5 (Spread of Flame) and Annex 2 (Surface Flammability / Heat Release) 1121
COLOURS AVAILABLE:		15 Shades

For more details/ clarification regarding technical specifications, handling and installation, please contact Responsive Flooring.
Note: The samples shown are representative. For technical reasons the material may vary in shades and appearance.
The pattern given are with their product codes.



The solution to every flooring need

Eucharistic Congress Building No.I, 5 Convent Street, Colaba, Mumbai 400 001, India.
 • India: Tel. +91 22 6656 2727 / 6656 2704 • India: Fax +91 22 6656 2798 / 6656 2799
 • USA: Tel. +1 732 7592843 • United Kingdom: Tel. +44 208 8199711
 • France: +33 1706 15499 • Australia: Tel. +61 29 0378599
 • E-mail: enquiry@responsiveindustries.com • URL: www.responsiveindustries.com