

Homogeneous Vinyl Flooring

Garnet®

How do you create a feel that's contemporary, and yet not avant-garde? With crushed patterns that breathe life into classic, neutral colours, to create an ambience at once trendy and classy.



1573-910-4



1573-909-4



1573-904-4



1573-905-4



1573-902-4

Key Features:

- No Wax, No Polish
- Polyurethane Reinforced (PUR)
- Low Maintenance Costs
- Anti Bacterial, Anti Fungi
- Light Colours
- Available up to 3.0 mm in Sheet & Tiles

Applications:


- Industrial Units
- Healthcare
- Laboratories
- Offices
- Shopping Centers etc.



1573-901-4



1573-903-4



1573-906-4



1573-908-4





1573-907-4



1573-905-4

The above texture is available in all colours.



























Welding Rod No. Garnet

- WR 1573-910-4
- WR 1573-909-4
- WR 1573-904-4
- WR 1573-905-4
- WR 1573-902-4
- WR 1573-901-4
- WR 1573-903-4
- WR 1573-906-4
- WR 1573-908-4
- WR 1573-907-4
- WR-Clear



The solution to every flooring need

Homogeneous Vinyl Flooring Garnet®

Technical Data		Garnet®
 GENERAL PERFORMANCE: EN 685 : 1996 EN 649 : 1997		<ul style="list-style-type: none"> • Homogeneous Single Layered Vinyl Flooring • Polyurethane Reinforced
 THICKNESS:	EN 428	2.00 mm 3.00 mm
 SHEET:	EN 426	2.0mm: 2m x 15m = 30m ² 3.0mm: 2m x 15m = 30m ²
 TILES:	EN 427	610mm x 610mm
 WEIGHT:	EN 430	2.0mm: 3.00 kg/m ² (Max.) 3.0mm: 4.50 kg/m ² (Max.)
 REACTION TO FIRE:	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2 ASTM E648-06	Class Bfl-S1 ≥ 8 kw/m ² Pass Type I
 FLEXIBILITY:	EN 435 ASTM F137	< 20mm Pass
 SLIP RESISTANCE:	EN 13893 DIN 51130	Class DS R10
 ABRASION RESISTANCE:	EN 660-2 ASTM D3384	Wear Group P Pass
 RESIDUAL INDENTATION:	EN 433 ASTM F970	< 0.1 mm Static load 800 psi
 CASTOR CHAIR:	EN 425	Continuous Use
 LIGHT FASTNESS:	EN 20105: B02	> Blue Wool Standard 6
 WEAR LAYER THICKNESS:	EN 429	2.0 mm, 3.0 mm
 ELECTRICAL BEHAVIOR (body voltage):	EN 1815	< 2.0 kV
 DIMENSIONAL STABILITY:	EN 434	<0.4 mm
 STAIN and CHEMICAL RESISTANCE:	EN 423	Good Resistance
 THERMAL RESISTANCE:	ISO 8302 (EN 12664)	< 0.00568 m ² K/W
 SMOKE DENSITY:	ASTM E 662-05	< 450
 FUNGI and BACTERIA RESISTANCE:		Does not favor growth
 CLEAN ROOMS:	ASTM F51/68	Class A - non-shedding Suitable for use in following classes of clean room: ISO 1466-11999 Class 4
 MARITIME USAGE:	IMO RES A 653 (16) IMO MSC 61 (67) US Coast Guard Approved Marine Equipment Directive	Annex 1 Part 2 (Smoke & Toxicity) Part 5 (Spread of Flame) and Annex 2 (Surface Flammability / Heat Release)  1121
 COLOURS AVAILABLE:		10 Shades

For more details / clarification regarding technical specifications, handling and installation, please contact Responsive Flooring.
Note: The samples shown are representative. For technical reasons the material may vary in shades and appearance.
The pattern given are with their product codes.



Eucharistic Congress Building No.I, 5 Convent Street, Colaba, Mumbai 400 001, India.
 • India: Tel. +91 22 6656 2727 / 6656 2704 • India: Fax +91 22 6656 2798 / 6656 2799
 • USA: Tel. +1 732 7592843 • United Kingdom: Tel. +44 208 8199711
 • France: +33 1706 15499 • Australia: Tel. +61 29 0378599
 • E-mail: enquiry@responsiveindustries.com • URL: www.responsiveindustries.com