

Heterogenous Vinyl Flooring

Zeta[®] Naos



It isn't about how old you are, it's about how young you feel. Cheeky, energetic and artistic patterns jolt staid, sober colours out of their monotony. Giving the room a flavour that's refreshingly youthful.

Key Features:

- No Wax, No Polish
- Wear Layer Polyurethane Reinforced (PUR)
- Multi Colours
- Scratch Resistant
- Anti Bacterial, Anti Fungi
- Available up to 3.0mm in Sheet & Tiles

Applications:

- Malls
- Homes
- Schools
- Restaurants
- Children Play Areas etc.



3374-565-4



3374-566-4



3374-551-4



3374-555-4



3374-556-4



3374-559-4




3374-561-4



3374-562-4



BIS



RvA



























Welding Rod No.
Zeta Naos

- WR 3374-565-4
- WR 3374-566-4
- WR 3374-551-4
- WR 3374-555-4
- WR 3374-556-4
- WR 3374-559-4
- WR 3374-561-4
- WR 3374-562-4
- WR-Clear



The solution to every flooring need

Technical Data		Zeta® Naos
 GENERAL PERFORMANCE: EN 685 : 1996 EN 649 : 1997		<ul style="list-style-type: none"> Homogeneous Single Layered Vinyl Flooring Wear Layer Polyurethane Reinforced
 THICKNESS:	EN 428	2.00 mm 3.00 mm
 SHEET:	EN 426	2.0mm: 2m x 15m = 30m ² 3.0mm: 2m x 15m = 30m ²
 TILES:	EN 427	610mm x 610mm
 WEIGHT:	EN 430	2.0mm: 3.50 kg/m ² (Max.) 3.0mm: 5.25 kg/m ² (Max.)
 REACTION TO FIRE:	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2 ASTM E648-06	Class Bfl-S1 ≥ 8 kw/m ² Pass Type I
 FLEXIBILITY:	EN 435 ASTM F137	< 20mm Pass
 SLIP RESISTANCE:	EN 13893 DIN 51130	Class DS R9
 ABRASION RESISTANCE:	EN 660-2 ASTM D3384	Wear Group T Pass
 RESIDUAL INDENTATION:	EN 433 ASTM F970 ASTM F1914	< 0.1 mm Pass Pass
 CASTOR CHAIR:	EN 425	Continuous Use
 LIGHT FASTNESS:	EN 20105: B02	> Blue Wool Standard 6
 WEAR LAYER THICKNESS:	EN 429 ASTM F410	0.50 mm, 0.70 mm Pass
 ELECTRICAL BEHAVIOR (body voltage):	EN 1815	< 2.0 kV
 DIMENSIONAL STABILITY:	EN 434	< 0.4 mm
 STAIN and CHEMICAL RESISTANCE:	EN 423 ASTM F925	Good Resistance Pass
 THERMAL RESISTANCE:	ISO 8302 (EN 12664)	< 0.00752 m ² K/W
 SMOKE DENSITY:	ASTM E 662-05	< 450
 FUNGI and BACTERIA RESISTANCE:		Does not favor growth
 CLEAN ROOMS:	ASTM F51/68	Class A - non-shedding Suitable for use in following classes of clean room: ISO 1466-11999 Class A
 MARITIME USAGE:	IMO RES A 653 (16) IMO MSC 61(67) US Coast Guard Approved Marine Equipment Directive	Annex 1 Part 2 (Smoke & Toxicity) Part 5 (Spread of Flame) and Annex 2 (Surface Flammability / Heat Release)  1121
 COLOURS AVAILABLE:		8 Shades

For more details/ clarification regarding technical specifications, handling and installation, please contact Responsive Flooring.
Note: The samples shown are representative. For technical reasons the material may vary in shades and appearance.
The pattern given are with their product codes.



Eucharistic Congress Building No.1, 5 Convent Street, Colaba, Mumbai 400 001, India.

- **India:** Tel. +91 22 6656 2727 / 6656 2704 • **India:** Fax +91 22 6656 2798 / 6656 2799
- **USA:** Tel. +1 732 7592843 • **United Kingdom:** Tel. +44 208 8199711
- **France:** +33 1706 15499 • **Australia:** Tel. +61 29 0378599
- E-mail: enquiry@responsiveindustries.com • URL: www.responsiveindustries.com