

Heterogenous Vinyl Flooring

Zeta[®] Spectra




There's something refreshing, relaxing about the rain. Here, raindrops flowing down a windowpane transform rigid pastels into fluid motifs, splashing drops of elegance and modernity into any room.

Key Features:

- No Wax, No Polish
- Wear Layer Polyurethane Reinforced (PUR)
- Pastel Shades
- Stain Resistant
- Durable & Tough
- Available up to 3.0mm in Sheet & Tiles

Applications:

- Retail Stores
- Education Centers
- Hotels
- Residential Communities
- Exhibition Centers etc.



4374-564-4



4374-563-4




4374-567-4



4374-565-4



4374-566-4




4374-569-4



4374-568-4



























4374-562-4



| |
|--|
| Welding Rod No. Zeta Spectra |
| WR 4374-564-4 |
| WR 4374-563-4 |
| WR 4374-567-4 |
| WR 4374-565-4 |
| WR 4374-566-4 |
| WR 4374-569-4 |
| WR 4374-568-4 |
| WR 4374-562-4 |
| WR-Clear |



The solution to every flooring need

| Technical Data | | Zeta [®] Spectra |
|---|---|---|
|  GENERAL PERFORMANCE: EN 685 : 1996 EN 649 : 1997 |  | <ul style="list-style-type: none"> Homogeneous Single Layered Vinyl Flooring Wear Layer Polyurethane Reinforced |
|  THICKNESS: | EN 428 | 2.00 mm 3.00 mm |
|  SHEET: | EN 426 | 2.0mm: 2m x 15m = 30m ² 3.0mm: 2m x 15m = 30m ² |
|  TILES: | EN 427 | 610mm x 610mm |
|  WEIGHT: | EN 430 | 2.0mm: 3.50 kg/m ² (Max.) 3.0mm: 5.25 kg/m ² (Max.) |
|  REACTION TO FIRE: | EN 13501-1 EN ISO 9239-1 EN ISO 11925-2 ASTM E648-06 | Class Bfl-S1 ≥ 8 kw/m ² Pass Type I |
|  FLEXIBILITY: | EN 435 ASTM F137 | < 20mm Pass |
|  SLIP RESISTANCE: | EN 13893 DIN 51130 | Class DS R9 |
|  ABRASION RESISTANCE: | EN 660-2 ASTM D3384 | Wear Group T Pass |
|  RESIDUAL INDENTATION: | EN 433 ASTM F970 ASTM F1914 | < 0.1 mm Pass Pass |
|  CASTOR CHAIR: | EN 425 | Continuous Use |
|  LIGHT FASTNESS: | EN 20105: B02 | > Blue Wool Standard 6 |
|  WEAR LAYER THICKNESS: | EN 429 ASTM F410 | 0.50 mm, 0.70 mm Pass |
|  ELECTRICAL BEHAVIOR (body voltage): | EN 1815 | < 2.0 kV |
|  DIMENSIONAL STABILITY: | EN 434 | < 0.4 mm |
|  STAIN and CHEMICAL RESISTANCE: | EN 423 ASTM F925 | Good Resistance Pass |
|  THERMAL RESISTANCE: | ISO 8302 (EN 12664) | < 0.00752 m ² K/W |
|  SMOKE DENSITY: | ASTM E 662-05 | < 450 |
|  FUNGI and BACTERIA RESISTANCE: | | Does not favor growth |
|  CLEAN ROOMS: | ASTM F51/68 | Class A - non-shedding Suitable for use in following classes of clean room: ISO 1466-11999 Class A |
|  MARITIME USAGE: | IMO RES A 653 (16) IMO MSC 61(67) US Coast Guard Approved Marine Equipment Directive | Annex 1 Part 2 (Smoke & Toxicity) Part 5 (Spread of Flame) and Annex 2 (Surface Flammability / Heat Release)  1121 |
|  COLOURS AVAILABLE: | | 8 Shades |

For more details/ clarification regarding technical specifications, handling and installation, please contact Responsive Flooring.
Note: The samples shown are representative. For technical reasons the material may vary in shades and appearance.
The pattern given are with their product codes.



Eucharistic Congress Building No.1, 5 Convent Street, Colaba, Mumbai 400 001, India.

- **India:** Tel. +91 22 6656 2727 / 6656 2704 • **India:** Fax +91 22 6656 2798 / 6656 2799
- **USA:** Tel. +1 732 7592843 • **United Kingdom:** Tel. +44 208 8199711
- **France:** +33 1706 15499 • **Australia:** Tel. +61 29 0378599
- E-mail: enquiry@responsiveindustries.com • URL: www.responsiveindustries.com